

MAGNASPORT



POWERSPORT BATTERY



Canada: 1-888-271-8888

www.magnacharge.com



USA: 1-844-370-0258

Model	Voltage (V)	Capacity (Ah) 10HR	CCA (-18°C) (A)	Inch (± 1/16 in)			Assembly Figure	Terminal Type	Reference Weight	
				L	W	H			kg	lbs
LITHIUM - Power Sports - 12V										
LITH-X4L	12	1.6	110	4.45	2.76	3.35	▬ □ □ □ ⊕	A	0.40	0.88
LITH-Z7S	12	2	140	4.45	2.76	3.35	▬ □ □ □ ⊕	A	0.50	1.10
LITH-9B	12	3	210	5.91	2.56	3.62	⊕ □ □ □ ▬	A	0.70	1.54
LITH-X9	12	3	210	5.91	3.43	4.13	⊕ □ □ □ ▬	A	0.70	1.54
LITH-Z10S	12	4	280	5.91	3.43	3.66	⊕ □ □ □ ▬	A	0.80	1.76
LITH-X12	12	3.5	250	5.91	3.43	3.66	⊕ □ □ □ ▬	A	0.70	1.54
LITH-12B	12	4.8	320	5.91	2.56	5.12	⊕ □ □ □ ▬	A	0.90	1.98
LITH-X14	12	4	280	5.91	3.43	3.66	⊕ □ □ □ ▬	A	0.80	1.76
LITH-Z14S	12	5	350	5.91	3.43	3.66	⊕ □ □ □ ▬	A	0.90	1.98
LITH-X20H	12	7	420	6.89	3.43	5.12	⊕ □ □ □ ▬	A	1.20	2.65
LITH-X20HL	12	7	420	6.89	3.43	5.12	▬ □ □ □ ⊕	A	1.20	2.65

AGM Maintenance Free DRY ** 2 Year Warranty **

Model	Voltage (V)	Capacity (Ah) 10HR	CCA (-18°C) (A)	Inch (± 1/16 in)			Assembly Figure	Terminal Type	Reference Weight	
				L	W	H			kg	lbs
High Performance, Factory Activated AGM Maintenance Free, Non-spillable - 12Volt										
MTX9-BS	12	8	120	5.91	3.43	4.13	⊕ □ □ □ ▬	A	3.10	6.83
MTX12-BS	12	10	180	5.91	3.43	5.12	⊕ □ □ □ ▬	A	4.10	9.03
MTX14L-BS	12	12	230	5.91	3.43	5.71	▬ □ □ □ ⊕	A	4.70	10.35
MTX14-BS	12	12	230	5.91	3.43	5.71	⊕ □ □ □ ▬	A	4.70	10.35
MTX14AHL-BS	12	12	240	5.28	3.50	6.46	▬ □ □ □ ⊕	A	5.30	11.67
MTX14AH-BS	12	12	240	5.28	3.50	6.46	⊕ □ □ □ ▬	A	5.30	11.67
MTX16LB-BS	12	19	350	6.89	3.94	6.10	▬ □ □ □ ⊕	A	7.50	16.52
MTX16B-BS	12	19	350	6.89	3.94	6.10	⊕ □ □ □ ▬	A	7.50	16.52
MTX50N18LA-BS	12	20	340	8.07	3.54	6.38	▬ □ □ □ ⊕	A	7.80	17.18
MTX20HL-BS	12	18	310	6.93	3.43	6.06	▬ □ □ □ ⊕	A	6.60	14.54
MTX20H-BS	12	18	310	6.93	3.43	6.06	⊕ □ □ □ ▬	A	6.60	14.54
MTX30L-BS	12	30	440	6.65	5.16	6.89	▬ □ □ □ ⊕	A	10.10	22.25

Factory Activated AGM Maintenance Free, Non-spillable - 12Volt										
YTZ7S	12	6	130	4.45	2.76	4.13	▬ □ □ □ ⊕	A	2.08	4.58
YTZ10S	12	8.6	190	5.91	3.43	3.66	⊕ □ □ □ ▬	A	2.91	6.41
YTZ12S	12	11	210	5.91	3.43	4.33	⊕ □ □ □ ▬	A	3.40	7.49
YTZ14S	12	11.2	230	5.91	3.43	4.33	⊕ □ □ □ ▬	A	3.57	7.86

Model	Voltage (V)	Capacity (Ah) 10HR	CCA (-18°C) (A)	Inch (± 1/16 in)			Assembly Figure	Terminal Type	Reference Weight	
				L	W	H			kg	lbs

High Performance, AGM Maintenance Free - 12Volt

YT4B-BS	12	2.3	40	4.45	1.50	3.35		J	0.92	2.03
YTX4L-BS	12	3	50	4.45	2.76	3.35		A	1.42	3.13
YTX5L-BS	12	4	70	4.45	2.76	4.13		A	1.80	3.97
YTX7L-BS	12	6	85	4.45	2.76	5.12		A	2.43	5.36
YTX7A-BS	12	6	90	5.91	3.43	3.66		A	2.52	5.56
YT7B-BS	12	6.5	85	5.91	2.56	3.66		A	2.34	5.16
YTX9-BS	12	8	120	5.91	3.43	4.13		A	3.09	6.81
YT9B-BS	12	8	115	5.91	2.68	4.13		A	2.80	6.17
YTX12-BS	12	10	180	5.91	3.43	5.12		A	3.97	8.75
YT12A-BS	12	10	175	5.91	3.46	4.13		A	3.32	7.32
YT12B-BS	12	10	175	5.91	2.72	5.12		A	3.63	8.00
YTX14L-BS	12	12	200	5.91	3.43	5.71		A	4.40	9.70
YTX14-BS	12	12	200	5.91	3.43	5.71		A	4.40	9.70
YT14B-BS	12	12	210	5.91	2.72	5.71		A	4.12	9.08
YTX14AHL-BS	12	12	210	5.31	3.54	6.57		A	4.71	10.39
YTX14AH-BS	12	12	210	5.31	3.54	6.57		A	4.71	10.39
YTX16L-BS	12	14	230	5.91	3.43	6.34		A	5.12	11.29
YTX16-BS	12	14	230	5.91	3.43	6.34		A	5.12	11.29
YTX16-BS-1	12	14	230	5.91	3.43	6.34		E	5.09	11.22
YTX20L-BS	12	18	270	6.89	3.43	6.10		A	6.07	13.38
YTX20-BS	12	18	270	6.89	3.43	6.10		A	6.07	13.38
YTX20HL-BS	12	18	310	6.89	3.43	6.10		A	6.07	13.38
YTX20H-BS	12	18	310	6.89	3.43	6.10		A	6.07	13.38
YTX20CH-BS	12	18	270	5.91	3.43	6.34		A	5.63	12.41
YTX24HL-BS	12	21	350	8.07	3.43	6.38		A	7.16	15.79
YIX30L	12	30	385	6.54	4.96	6.81		A	9.93	21.90

PLATINUM O.E. High Performance

YB2.5L-C	12	2.5	19	3.15	2.76	4.13		/	1.08	2.38
YB3L-A	12	3	32	3.86	2.20	4.33		B	1.24	2.74
YB3L-B	12	3	32	3.86	2.20	4.33		B	1.24	2.74
YB4L-B	12	4	56	4.72	2.76	3.62		A	1.58	3.47
YB4L-A	12	4	56	4.72	2.76	3.62		A	1.58	3.47
YB5L-B	12	5	65	4.72	2.36	5.12		B	2.06	4.55
YB7B-B	12	7	124	5.91	2.36	5.12		B	2.63	5.79
YB7C-A	12	8	124	5.12	3.54	4.49		E	2.84	6.27
YB9-B	12	9	130	5.31	2.95	5.47		B	2.99	6.59
YB9L-B	12	9	130	5.31	2.95	5.47		B	2.99	6.59
YB9L-A2	12	9	124	5.31	2.95	5.47		A	2.99	6.59
YB9A-A	12	9	130	5.31	2.95	6.10		B	2.99	6.59
YB10L-B	12	11	160	5.31	3.54	5.71		B	3.73	8.23
YB10L-B2	12	11	160	5.31	3.54	5.71		D	3.73	8.23
YB12A-A	12	12	165	5.28	3.15	6.30		B	4.06	8.94
YB12AL-A	12	12	165	5.28	3.15	6.30		B	4.06	8.94
YB12AL-A2	12	12	165	5.28	3.15	6.30		B	4.06	8.94
YB12B-B2	12	12	165	6.30	3.54	5.12		D	3.94	8.68
YB12C-A	12	12	165	5.28	3.15	6.89		A	4.08	8.99
YB14-A2	12	14	190	5.28	3.50	6.54		D	4.61	10.15
YB14-B2	12	14	190	5.28	3.50	6.54		D	4.61	10.15
YB14L-A1	12	14	190	5.28	3.50	6.54		E	4.61	10.15
YB14L-A2	12	14	190	5.28	3.50	6.54		D	4.61	10.15

